



860 Series

Heat Shrink Tunnels

Standard Features:

All 860 Heat Shrink Tunnels

- Chamber opening - 15"W x 60"L x 8"H (38cm x 152cm x 20cm)
- 13,500 watts of heating power
- 220V, three phase
- Variable speed conveyor
- Fully insulated heat chamber
- Control panel on the outside of the heat chamber for longer component lifespan
- Digital precision temperature control
- Automatic cool down
- Air direction controls
- Variable air velocity control
- High efficiency finned rod heating elements
- Bottom air flow heat transfer system
- Adjustable levelers
- One year limited warranty



860 Heat Shrink Tunnel

- Variable speed 84"L, quick adjusting, live/dead roller conveyor

860MB Heat Shrink Tunnel

- Variable speed 84"L Teflon coated fiberglass mesh conveyor

Optional Features:

- 1.5" or 1" roller spacing (853 only)
- Locking casters

Other Features:

- Heavy gauge steel construction
- Made in USA

Specifications & Designs may change without notice ♦ Some photos may show accessories not part of basic machine ♦ Pricing does not include taxes, shipping & handling or installation

Your ultimate source for packaging materials & equipment

HSA PACKAGING SYSTEMS

21500 Blythe Street, Canoga Park, CA 91304

Tel: (818) 712-0100; Toll Free: (800) 326 5937 ; Fax: (818) 712-0470

Email: sales@hsapackaging.com; Web: www.hsapackaging.com

Copyright © 2003-2009 Manakz Corporation. All rights reserved. Reproduction without prior written permission prohibited